



	PB-0008	PB-0009	PB-0013	PB-0014	PB-0015	PB-0017	PB-0140	PB-0150	PB-0160	PB-0170	PB-0180	PB-0181	PB-0182	PB-0187
介质 Medium	已过滤，润滑型 / 未润滑型压缩空气 Filtered, lubricated / non lubricated compressed air													
压力范围 Pressure range	2.5 + 8 bar													
温度范围 Temperature range	5 + 60 °C.													
行程 (±2°) Stroke	2x10°	2x10°	2x15°	2x15°	2x16°	2x15°	2x15°	2x15°	2x15°	2x15°	2x15°	2x15°	2x15°	2x15°
每一钳口在6 bar压力下的关闭扭矩 Closing gripping torque at 6 bar each jaw	24 Ncm	24 Ncm	80 Ncm	80 Ncm	60 Ncm	80 Ncm	80 Ncm	80 Ncm	80 Ncm	80 Ncm	80 Ncm	80 Ncm	80 Ncm	80 Ncm
每一钳口在6 bar压力下的打开扭矩 Opening gripping torque (at 6 bar) each jaw	2 Ncm	2 Ncm	5 Ncm	5 Ncm	5 Ncm (25 Ncm)	5 Ncm	5 Ncm	5 Ncm	5 Ncm	5 Ncm	5 Ncm	5 Ncm	5 Ncm	5 Ncm
最大工作频率 Maximum working frequency	3 Hz													
循环空气消耗量 Cycle air consumption	0.3 cm ³	0.3 cm ³	1.2 cm ³	1.2 cm ³	1.5 cm ³	1.2 cm ³	1.2 cm ³	1.2 cm ³	1.2 cm ³	1.2 cm ³	1.2 cm ³	1.2 cm ³	1.2 cm ³	1.2 cm ³
空载关闭时间 Closing time without load	0.01 s													
重量 Weight	15 g	25 g	55 g	50 g	50 g	45 g	75 g	75 g	75 g	50 g	60 g	75 g	75 g	57 g